



SWS7683W



Ensure a reliable connection

with this 3-way manual switcher

Manually switch between three scart input sources using A, B, C push buttons. 2x shielding cable for transferring audio/video signals between your components.

Enjoy better picture/sound quality

• 24 carat gold-plated connectors optimize signal

Protects against signal loss

· Copper braided reinforced aluminum shielding

Easy installation

- Non-slip ergonomic grip for easy use
- · Plug and play for easy use

Enjoy extended durability

• Flexible PVC jacket

Environmentally friendly

• Environmentally friendly lead-free construction



SWS7683W/10

Specifications

Inner Carton

- Gross weight: 1.434 kg
- Inner carton (L x W x H): 20.6 x 13 x 40.6 cm
- Nett weight: .984 kg Tare weight: .45 kg

Outer Carton

- Gross weight: 9.614 kg
 Outer carton (L x W x H): 43.8 x 40.6 x 41.9 cm
- Nett weight: 5.904 kg • Tare weight: 3.71 kg

Packaging dimensions

- Packaging dimensions (W \times H \times D): 19.5 \times 23.5 \times 5.4 cm
- Gross weight: .328 kg • Nett weight: .246 kg
- Tare weight: .082 kg

Highlights

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

Braided shielding

Copper braided reinforced aluminum shielding protects against signal loss and interference.

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.



Issue date 2009-04-14

Version: 1.1.4

© 2009 Koninklijke Philips Electronics N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

12 NC: 8670 000 39738 EAN: 87 12581 42314 8

www.philips.com